# LaTeX News

Issue 5, June 1996

## *Welcome to LaTeX News 5*

This issue of *LaTeX News* accompanies the fifth release of the new standard LaTeX, LaTeX 2$_\varepsilon$.

## *Extra possibilities for section headings*

Most LaTeX sectioning commands are defined using `\@startsection`. For example, the article class defines:

```
\newcommand\section{\@startsection
 {section}{1}{0pt}{-3.5ex plus-1ex minus-.2ex}%
 {2.3ex plus.2ex}{\normalfont\Large\bfseries}}
```

The last argument specifies the style in which the section heading is to be typeset.

The new feature added at this release is that at the *end* of this argument you may specify a command that *takes an argument*. This command will be applied to the section number and heading. For example, one could use the `\MakeUppercase` command to produce uppercase headings. A package or class file could contain:

```
\renewcommand\section{\@startsection
 {section}{1}{0pt}{-3.5ex plus-1ex minus-.2ex}%
 {2.3ex plus.2ex}{\normalfont\Large\MakeUppercase}}
```

to produce section headings using uppercase medium weight text, rather than the bold text used by article. Note that, like the font choice, the uppercasing applies only to the actual heading (including any automatically generated section number), not to the text as it may appear in the running head or table of contents.

## *The 'openany' option in the 'book' class*

The openany option allows chapter and similar openings to occur on left hand pages. Previously this option only affected `\chapter` and `\backmatter`. It now also affects `\part`, `\frontmatter` and `\mainmatter`.

## *More font (output) encodings*

The font encoding name `T3` has been allocated to the encoding used in the new 256-character IPA fonts (for the phonetic alphabet) produced by Rei Fukui. His package, tipa, gives access to these fonts and should soon be available. (The encoding named `OT3` is the 128-character encoding used in the IPA fonts produced by Washington State University.)

## *More input encodings supported*

The inputenc package now supports the IBM codepage 852 used in Eastern Europe, with the option `[cp852]` contributed by Petr Sojka.

Also, the inputenc package now activates most 'control codes' with ASCII values below 32. Currently none of the encodings in the standard distribution makes use of these positions.

## *Fixes and improvements*

The LaTeX kernel has only had minor changes, apart from `\@startsection` mentioned above. However, some small fixes have been incorporated removing the following problems:

- In tabular and array, previous versions of LaTeX 'lost' the inter-column space from an '`l`'-column, when that column was completely empty.
- Previously, the use of the `\nofiles` command could change the *vertical spacing* in a document. A side effect of fixing this is that when `\nofiles` is used, `\label` puts a blank line in the log file.
- LaTeX often loads fonts 'on demand'. Previously, this could happen inside the argument of an accent command and this would cause the accent to appear in the wrong place.

## *Changes to the 'tools' packages*

- The longtable package now uses a modified algorithm, contributed by David Kastrup, to align the 'chunks' of a table. It is now unnecessary to edit the document to add `\setlongtables` before the final run of LaTeX. In certain cases of overlapping `\multicolumn` entries, the new algorithm will produce better column widths than the old (at the price of extra passes through LaTeX).
- The dcolumn package now has the extra possibility of specifying the number of digits both *before* and after the 'decimal point'. This makes it easy to centre the column of numbers under a wide heading.

## *New copy of the LaTeX bug database*

`http://www.tex.ac.uk/ctan/latex/bugs.html` will soon have links to a copy of the searchable LaTeX bugs database at Mainz (Germany) as well as the original copy at Sussex (England).

LaTeX News, and the LaTeX software, are brought to you by the LaTeX3 Project Team; Copyright 1996, all rights reserved.